



EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA
PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉFOS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16

FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



REPLEX - 80

OUTDOOR AND INDOOR PLASTIC PLASTER

General:

REPLEX is a plaster or wall lining for interior and exterior, manufactured based on aqueous dispersions of synthetic copolymers, combined with quartz and inorganic charge that allowing cover small cracks that may have a surface on which it will be apply.

REPLEX offers various possibilities of rugged and embossing effects, as the tool used in its application, achieving very hard coatings with high resistance to abrasion and shock.

REPLEX is a very appropriate product to enhance its finish with our pearly Varnish (Gold and Silver).

TECHNICAL INFORMATION

Aspect.....	MATTE
Color.....	ACC CHART
Density.....	1,7 Kg/Lt.
Viscosity.....	THIXOTROPIC
Recommended thickness.....	ACC FINISH
Theoretical performance.....	0,5 - 1 M ² /Kg.
Drying 20 °C/70% RH	
Touch.....	1 - 2 HOURS
Repaint.....	3 - 4 HOURS

APPLICATION INSTRUCTIONS:

- **Method**
Brush, Roller, Airbrush gun or Air-Less.
- **Dilution**
If necessary use only water.
- **Cleaning**
After use, clean all equipment with water, preferably hot.

SURFACES PREPARATION:

Before applying REPLEX, adhesion and imperfections must be eliminated, sanding and cleaning to remove nitrate deposits, grease, old paints, dust, etc.. It is recommended use a sealant before, on both new and old surfaces, and after 24 hours apply one or two coats of REPLEX.

HYGIENE AND SECURITY:

- Non-flammable product.
- Because its solvent is water, no toxicity problems whatsoever. It contains no toxic components.
- In case of eyes contact, wash with plenty of water
- Storage: up to a year in places protected from frost. If the packaging has been opened, close it well and use it within 30 days.
- If the product splashes eyes, rinse with water several times; always consult your doctor or the National Institute of Toxicology, Phone Number 91 – 562.84.69.

Comments

- * When performance practical calculation take place it is necessary to be considered product losses by surface irregularities and application system.
- * The solvent addiction proportionally modifies the solid content in the paint and therefore the thickness of wet film.
- * Our Technical Department will be pleased to answer as many as questions that you are planning to ask.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.