



EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959
 POLÍGONO DE SALCEDO - 33120 PRAVIA
 PRINCIPADO DE ASTURIAS (ESPAÑA)
 TELÉF.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16
 FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS
 E-mail: eupines@terra.es



B. A. P. – 898 – W

HIGH PENETRATION VARNISH

PRODUCT DESCRIPTION:

- **DEFINITION:** Formulated based on acrylic-synthetic resins in dispersion, its microporous character allows the penetration into the wood, and not forming layers, prevents the appearance of cracks, alligating and flaking. Its perfect transparency allows see the grain of the wood.
- **USE:** Decorates, protects and beautifies wooden houses, doors, windows, fences, etc. both exterior and interior. It repels water, dust and dirt. Regulates humidity and compensates the wood natural movement. It provides texture to the wood interior.
- **PROPERTIES:** Protects the wood against the destructive action of UV ray, environments such as contaminated, aggressive, marine and mountaineering, as well as fungi attacks, woodworms and humidity.

TECHNICAL INFORMATION

Aspect..... MATTE, SATIN
 Color..... ACC/ CHART
 Density..... 0,84 Kg/Lt.
 Viscosity..... 12" Ford cup -4 to 20C°
 Recommended thickness..... 20 micron
 Theoretical performance..... 10 - 12 M²/Lt.
 Drying 20 °C/70% RH
 Touch..... 1 hour
 Repaint..... 1 - 2 hours

APPLICATION INSTRUCTIONS:

- **Method**
Brush, Roller, Airbrush gun and Air-Less.
- **Dilution**
Ready to use.
- **Cleaning**
After use, clean all equipment with our S.G. Solvent.

SURFACES PREPARATION:

- Before applying stir well the product to the perfect homogeneity.
- The wood must be clean, dry and degreased, although not necessary, a previous sanding improve performance.
- **INTERNAL AND EXTERNAL SURFACES:** give one coat of BAP - 898 - W if you want a matte aspect and two coats when you want to get a silky-satin finish.

HYGIENE AND SECURITY:

- Being a flammable product, keep away from sparks and flames.
- It is recommended the most appropriate respiratory protection to each case by the corresponding mask.
- Avoid prolonged inhalation of solvent vapors.
- During the application have adequate ventilation and maintain a constant air renewal.
- Avoid eye and skin contact, if product comes in contact with skin, wash with soap and water.
- If the product splashes eyes, rinse with water several times; always consult your doctor or the National Institute of Toxicology, Phone Number 91 – 562.84.69.

Comment

- * When performance practical calculation take place it is necessary to be considered product losses by surface irregularities and application system.
- * The solvent addition proportionally modifies the solid content in the paint and therefore the thickness of wet film.
- * Our Technical Department will be pleased to answer as many as questions that you are planning to ask.

This product can be stored up to one year, if the packaging has been opened close properly and used as soon as possible.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.