

























EUROPEA DE PINTURAS ESPECIALES, S.L. C LF B/33 124 959 POLÍGONO DE SALCEDO - 33120 PRAVIA PRINCIPADO DE ASTURIAS (ESPAÑA) TELÉFS.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16 FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS E-mail: eupines@terra.es













## CLEANING SOLVENT S. G.

## PRODUCT DESCRIPTION:

• DEFINITION: It is a solvent type: S.G. compatible for cleaning all types of synthetic paints, nitro, chlorinated rubber,

polyurethane, epoxies, etc.

• USE: It is formulated with a blend of aromatic hydrocarbons, ethyl glycol acetates, ketones, toluene, alcohols,

• PROPERTIES: Only in cases of utmost necessity and not more than 5%, can be used for mixtures and solutions of synthetic

paints and alkyd. It's most common use is to clean all types of tools, circuits and equipment used in the

application.

## TECHNICAL INFORMATION

Color.....COLORLESS

Physical state.....LIQUID - VOLATILE

Odor......PLEASANT

Miscible with water and more mild than this Density......  $0,80 - 0,85 \% \pm 1 \%$ 

Flash point......3,5° C  $\pm$  1 %

Ignition temperature......500° C  $\pm$  1 % Melting point.....94° C  $\pm$  1 %

## **HYGIENE AND SECURITY:**

- Being a flammable product, keep away from sparks and flames.
- Avoid prolonged inhalation of solvent vapors.
- Avoid eye and skin contact. Danger of poisoning by ingestion
- If product comes in contact with skin, wash with soap and water.
- If product comes in contact with skin, wash thoroughly with soap and warm water.
- If the product splashes eyes, rinse with water several times; always consult your doctor or the National Institute of Toxicology, Phone Number 91 - 562.84.69.
- Explosive container when heated.
- In case of spillage, prevent sparks or flames, seeking to cut the fire with sand.
- In case of fire, extinguish with foam or chemical powder, but never with water.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.