



EUROPEA DE PINTURAS ESPECIALES, S.L.

C.I.F. B/33.124.959

POLÍGONO DE SALCEDO - 33120 PRAVIA

PRINCIPADO DE ASTURIAS (ESPAÑA)

TELÉF.: 98 582 21 39 / 98 582 20 61 / 98 582 22 16

FAX 98 582 22 16 - APARTADO 311 - 33400 AVILÉS

E-mail: eupines@terra.es



MOVITOL - 120 UNIVERSAL LOOSEN

PRODUCT DESCRIPTION:

- **DEFINITION:** LOOSEN of exceptional penetrating power, because with its high degree of introduction, unblock in the shortest space of time all kinds of items blocked by rust. It has great penetrability in all types of metal surfaces. Its strong oxidant and penetrating action permits instantaneous unlocks stiff elements by oxide.
- **USE:** It is a product of great use in the Assembly and Maintenance Departments of any industry: Iron and Steel, Mining, Marine, Transport, Services, Chemical Plant, Hydroelectric, Thermal, Nuclear, etc., and even in domestic and family environments. It is used to easily unlock mechanical parts that can usually offer more resistance, such as: nuts, screws, shafts, pistons, etc.
- **PROPERTIES:** Formidable fixed oxide dispersant produced in highly corrosive, industrial and marine environment. Extraordinary unblock for all types of work and as an active anti-static high-power unblock. It is a liquid that for its special characteristics, scattered rust, unlocked at high speed, loosen all types of nuts, bolts and pieces: dissolves rust, acts as a cleaner oil, has high descaler power and provides the following advantages: great time and personnel savings, recovery of obsolete parts, easy application, avoid replacements, optimum service, it offers no risk of application or known incompatibility.
- **PROCESS OF USE:** Depends on work type and consists of pouring a small amount of MOVITOL - 120 over extraction areas or penetration grooves on immobilized organisms or parts. After a few minutes and by the usual procedure, proceed to dismantling them. If the problem to treat was of large-scale, can choose to repeat this operation several times or to unlock by immersion if the piece permits, may also in some cases appealing to apply to the surface large pieces of cotton wool or clean rags soaked in MOVITOL - 120, hitting the side walls with blows at intervals, in order to get some open crack where it can penetrate.

TECHNICAL INFORMATION

Aspect.....	OIL LIQUID
Color.....	DARK
Density.....	0,82 gr. / c.c.
Dry extract 100° C.....	65 ± 2%
Flashpoint (° C).....	54
Viscosity 40° C (CST).....	3,5 ± 2%
Freezing point (° C).....	- 20

APPLICATION INSTRUCTIONS:

- **Application Method**
Paintbrush, Brush, Roller, Spray gun, Pulverizer, Spray or immersion.
- **Cleaning**
After use, clean all equipment with our S. G. Solvent.
- **Presentation**
1, 5, 25, 50 and 200 Lt.
Sprays of 270 c.c. and 520 c.c.

HYGIENE AND SECURITY:

- Being a flammable product, keep away from sparks and flames.
- It is recommended the most appropriate respiratory protection to each case by the corresponding mask.
- Avoid prolonged inhalation of solvent vapors.
- During the application have adequate ventilation and maintain a constant air renewal.
- Avoid eye and skin contact, if product comes in contact with skin, wash with soap and water.
- If the product splashes eyes, rinse with water several times; always consult your doctor or the National Institute of Toxicology, Phone Number 91 – 562.84.69.

Our technical service is at your disposal for further information in this booklet as well as to advise on special treatments, systems, process and the best products, according to the surface, environments and needs they wish to cover.

In this sheet, we just trying to inform and advice to our best knowledge, based on experience and research. We cannot be responsible for the consequences of using this product when application conditions and circumstances fall out of our reach and control.